





## NOTES:

- 1. DIMENSIONS ARE FOR REFERENCE ONLY • DIMENSIONS IN [ ] ARE mm
- 2. PIN LOCATIONS ARE ±.005" [.13 mm] FROM CENTER

MATERIAL:	DESIGN	JEF	11/02/06
-	DRAWN	JEF	11/02/06
FINISH:	CHECKED	-	-
	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES, DIAMETERS CONCENTRIC: .003 TIR, FACES PERPENDICULAR: .003 INTERPRETATION PER ASME Y14.5M-1994 REMOVE ALL BURRS AND BREAK		
THIRD ANGLE PROJECTION			
	CHARD EDGES OUR LOID A 166 VII		

P14.5M-1994
REMOVE ALL BURRS AND BREAK
SHARP EDGES .005/.010 X 45°, ALL
INSIDE CORNERS TO BE .02 R MAX.
TOLERANCES:
.XX ± .01 FRAC. ± 1/64"
.XXX ± .005 ANG. ± 1°
SURFACE FINISH 125 RMS MAX. U.O.S. THIS DRAWING AND SPECIFICATION
CONTAINS PROPRIETARY INFORMATION
TO MAGTROL INC. ANY DISCLOSURE
OR REPRODUCTION OF THIS DOCUMENT WITHOUT WRITTEN AUTHORIZATION FROM MAGTROL INC. IS EXPRESSLY PROHIBITED



70 GARDENVILLE PKWY, W. BUFFALO, NEW YORK 14224-1322

CB-800, CAL BEAM ASSY FOR HD-800 SERIES DYNOS

USED ON: -SIMILAR TO: 400800

DWG. NO.

REV 400801

B SCALE SHEET # 1:2 2 OF 2