

Customized Test System for Starter Motors

APPLICATION

This CMTS is designed for starters with 12-volt DC motors, direct drive output for up to 12,000 rpm, up to 100 lb·in (11.3 N·m) and 750 amps peak current draw. Starter motors are very powerful for short periods of time and draw very high current.

COMPONENTS

- Heavy-Duty Equipment Rack: with plug panel
- Dynamometer Table
- HD-800 Hysteresis Dynamometer
- DSP6001 High-Speed Programmable Dynamometer Controller
- M-TEST 4.0 Motor Testing Software
- 6510e Single-Phase Power Analyzer
- Power Supply (830 A)
- PC, Monitor, Keyboard

CUSTOM FRONT PANEL

In the front of the equipment rack, a three-position power lead plug panel is provided to select the appropriate current shunt for the most suitable measurement range.

FUTURE MODIFICATIONS

This system is expected to have a second fixture added in the near future for testing high torque motors used to shift automatic 4-wheel drive transmissions into 4WD at the push of a button. Magtrol will then add a PB 115 Magnetic Powder Dynamometer to the existing CMTS.





MAGTROL INC

70 Gardenville Parkway Buffalo, New York 14224 USA Phone: +1 716 668 5555 Fax: +1 716 668 8705

E-mail: magtrol@magtrol.com

MAGTROL SA

Centre technologique Montena 1728 Rossens/Fribourg, Switzerland Phone: +41 (0)26 407 3000 Fax: +41 (0)26 407 3001 E-mail: magtrol@magtrol.ch

www.magtrol.com

Subsidiaries in:

Great Britain Germany • France China • India

Worldwide Network of Sales Agents

